



**COLEMAN-MACH
DATA INQUIRY SHEET
452X3*8XX3
MACH 10 – 13.5K A/C NDQ**

Capacity (Nominal)	Cooling Heating(1)	13,500 5,600
Electrical Rating	115 VAC, 60 HZ, 1 Phase	
Cooling Full Load AMP's at A.R.I. Standard Condition	Compressor Fan Motor Total	8.7 Low – 1.2 High – 1.7 9.9 10.4
Feature Equipment Amps	Heating (1)	16
Running Watts (Cooling) A.R.I. Standard Condition (80° F. DB/67° F. WB Indoor, 95° F. DB Outdoor)	1216	
Running Watts (Cooling) Maximum Condition (100° F. DB/72° F. WB Indoor, 120° F. DB Outdoor)	1500	
Running Watts (Heating) (1)	1800	
Compressor Locked Rotor Amps	45.5	
Metering Device	Capillary Tube	
Refrigerant Charge (R410A)	15.00 oz	
Evaporator Air Delivery (High Speed)	265 cfm	
Generator Size	See “Generators” Below	
Unit Weight (2)	80 lbs. (2)	
Use time delay fuse or circuit breaker (U.L. H.A.C.R. Type C.S.A.) Rated at: Minimum 15 Amps; Minimum (1) 20 Amps; Maximum 20 Amps. See Product Installations for proper wire sizes.		

- (1) When equipped with Elect-A-Heat feature.
- (2) Ceiling assemblies may add an additional 3.5 to 12.5 lbs. depending on the model number.

CEILING ASSEMBLY: Any 9430 series C/A


GENERATORS:

It is not the policy of Airxcel, Inc. to size generators for application in Recreation Vehicles or related structures. However, when sizing generators, the total electrical power consumption in Watts must be determined and taken into consideration, such as:


- A. Maximum running watts of the air conditioner at Airxcel, Inc. Desert Test (See Specifications).
- B. Power consumption of electronic ovens, toasters, coffeemakers, television sets, refrigerators, lights, etc.
- C. Generators do lose capacity under the following conditions: (1) Altitude increases above sea level, (2) Temperature increases above certain outdoor design temperatures, and (3) Lack of maintenance.

Airxcel, Inc.
RV Products Division
P.O. Box 4020
Wichita, KS 67204

ROOF TOP UNIT DIMENSIONS



CEILING SHROUD DIMENSIONS



QUICK REFERENCE CHART

DIMENSIONS (mm/inches)		
Exterior Shroud	Height	11.8
	Width	26.2
	Length	38.0
Interior Shroud	Depth	2.2
	Width	21.0
	Length	22.1



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.