



RV Products Division

**COLEMAN-MACH  
DATA INQUIRY SHEET  
492X3\*87X  
POLAR MACH**

|                                                                                                                           |                                                                        |
|---------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|
| Capacity (Nominal BTUH)                                                                                                   | Cooling/Heating 13,500<br>Heating (1) 5,600                            |
| Electrical Rating                                                                                                         | 115 VAC, 60 HZ, 1 Phase                                                |
| Cooling Full Load AMP's at A.R.I. Standard Condition                                                                      | Compressor 11.8<br>Fan Motor Low – 3.65 High – 3.8<br>Total 15.45 15.6 |
| Feature Equipment Amps                                                                                                    | Heating (1) 16.4                                                       |
| Running Watts (cooling) A.R.I. Standard Condition (80 F. DB 67 F. WB Indoor, 95 F. DB Outdoor)                            | 1640                                                                   |
| Running Watts (cooling) Desert Condition (100 F. DB 72 F. WB Indoor, 120F. DB Outdoor)                                    | 2000                                                                   |
| Running Watts (heating) (1)                                                                                               | 1800                                                                   |
| Compressor Locked Rotor Amps                                                                                              | 63                                                                     |
| Metering Device                                                                                                           | Capillary Tube                                                         |
| Refrigerant Charge – R-410A                                                                                               | 22.50 oz.                                                              |
| Evaporator Air Delivery (CFM)                                                                                             | 310 – High Speed                                                       |
| Generator Size                                                                                                            | See “Generators” Below                                                 |
| Unit Weight (pounds)                                                                                                      | 95 lbs. (2)                                                            |
| Use time delay fuse or circuit breaker (U.L. H.A.C.R. Type C.S.A.) Rated at 20 amps.<br>Supply wires 12 AWG Min. (Copper) |                                                                        |

- (1) When equipped with Elect-A-Heat feature.
- (2) Ceiling assemblies may add an additional 3.5 to 12.5 lbs. depending on the model number.

**CEILING ASSEMBLY:** Any 8330, 9330, 7330B751, -755 and 7530B750


**GENERATORS:**

It is not the policy of Airxcel, Inc. to size generators for application in Recreation Vehicles or related structures. However, when sizing generators, the total electrical power consumption in Watts must be determined and taken into consideration, such as:

- A. Maximum running watts of the air conditioner at Airxcel, Inc. Desert Test (See Specifications).
- B. Power consumption of electronic ovens, toasters, coffeemakers, television sets, refrigerators, lights, etc.
- C. Generators do lose capacity under the following conditions: (1) Altitude increases above sea level, (2) Temperature increases above certain outdoor design temperatures, and (3) Lack of maintenance.

**Airxcel Inc.  
RV Products Division  
P.O. Box 4020  
Wichita, KS 67204**


## ROOF TOP UNIT DIMENSIONS



## QUICK REFERENCE CHART

| DIMENSIONS      |        |       |
|-----------------|--------|-------|
| Exterior Shroud | Height | 10.63 |
|                 | Width  | 30.25 |
|                 | Length | 44.00 |
| Interior Shroud | Depth  | 2.2   |
|                 | Width  | 19.9  |
|                 | Length | 20.1  |

## CEILING SHROUD DIMENSIONS



---



---

# This manual is provided courtesy of **RV Tech Cheat Sheet**



**Professional resources for the whole RV industry — free.**

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.

---



---

**[rvtechcheatsheet.com/manuals](https://rvtechcheatsheet.com/manuals)**

**Find thousands more RV manuals, wiring diagrams and parts lists**

**RV techs:** share fixes, ask questions and learn from each other.

**Join our free Facebook group →**

---



---

Follow proper safety practices. If in doubt, consult a professional RV technician.