

# INSTALLATION INSTRUCTIONS

**WARNING: NEVER EXCEED YOUR VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY**

## CARGO CARRIER BAG



## WARNINGS

Read manual carefully before installation or use of this product. The warnings, cautions and instructions discussed in this instruction manual cannot cover all possible conditions or situations that could occur. It must be understood by the operator that common sense and caution are factors which cannot be built into the product and are the responsibility of the end user.

This expandable cargo bag is designed to mount to an existing hitch-mounted cargo carrier. Lashing straps hold the cargo storage bag to the cargo carrier.

If the cargo carrier or contents being transported are in line with the exhaust outlet, an exhaust tip must be used to redirect the exhaust flow away from the cargo platform or contents.

When traveling, periodically check straps to ensure load is securely held. Any excess webbing should be tucked away and tied off to prevent flapping while driving.

After removing contents from the cargo storage bag, remove unit from the cargo carrier and store for safekeeping. Do not leave empty cargo storage bag on vehicle.

Do not exceed the cargo carriers rated load capacity.

## MAINTENANCE

It is recommended that the general condition of any cargo bag be examined before it is used. Keep the cargo bag in good repair. Have necessary repairs made by qualified service personnel.

## ASSEMBLY

### Step 1

Spread out the cargo storage bag onto the cargo carrier so that the bag opens to the rear.

### Step 2

Unzip the cargo bag and begin loading, placing the larger, heavier objects in first. Continue to load the bag, placing smaller, lighter items on the top to create a compact load.

### Step 3

Close the zipper, making sure the flap is pulled down to completely cover the entire zipper. Seal the bag with the provided hook and loop closures.

### Step 4

Attach the long end of the lashing straps to the buckles on the top of the cargo bag, as shown in Figure 1.

### Step 5

Attach the short ends of lashing straps to the cargo carrier, as shown in Figure 2.

### Step 6

Take up slack in straps until the cargo bag is securely attached to the cargo carrier.




Figure 1




Figure 2



---



---

# This manual is provided courtesy of **RV Tech Cheat Sheet**



**Professional resources for the whole RV industry — free.**

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.

---



---

**[rvtechcheatsheet.com/manuals](https://rvtechcheatsheet.com/manuals)**

**Find thousands more RV manuals, wiring diagrams and parts lists**

**RV techs:** share fixes, ask questions and learn from each other.

**Join our free Facebook group →**

---



---

Follow proper safety practices. If in doubt, consult a professional RV technician.