

FURRION

5" 2-WAY OUTDOOR MARINE SPEAKER WITH LED

FMS5XX



FMS5L2-BL



FMS5L2-PS



UV RESISTANT



IP55
WATERPROOF

PP reinforced cone extends frequency response and minimizes distortion; this controls rigidity and internal damping and creates high definition audio with a pure, distinct sound.

[illegible]

Technical drawings of the steering wheel and horn button. The steering wheel is shown from the front and side. The front view shows a three-spoke design with a central hub. The side view shows the thickness of the wheel. The horn button is shown from the front and side. The front view shows a circular button with a central hub. The side view shows the thickness of the button. Dimensions are provided in inches and millimeters.

Steering wheel dimensions:

- Outer diameter: $1\frac{1}{4}$ " [32mm]
- Spoke width: $\frac{3}{16}$ " [4.2mm]
- Side view thickness: $\frac{1}{2}$ " [12.7mm]
- Center hub diameter: $\frac{9}{16}$ " [7.8mm]

Horn button dimensions:

- Outer diameter: $1\frac{1}{8}$ " [40mm]
- Side view thickness: $\frac{1}{2}$ " [12.3mm]
- Center hub diameter: $\frac{7}{16}$ " [10mm]

[illegible]

Technical drawings of the 100mm diameter flange for the 100mm x 100mm x 10mm plate. The drawings show the front, side, and back views with dimensions in inches and millimeters.

- Front View (Left):** Shows a circular flange with a central hole of 100mm diameter. The outer diameter is 7 1/4" (197mm). The flange has a thickness of 3/16" (4.5mm) and a central hole of 1/8" (3.6mm). The distance from the center to the outer edge is 5 1/2" (140mm). The distance from the center to the inner hole is 3 3/4" (99mm). The distance from the center to the outer edge of the flange is 3 3/4" (99mm).
- Side View (Middle):** Shows the flange profile with a height of 6 3/8" (172.1mm) and a width of 6" (151.6mm). The flange has a thickness of 1 1/4" (48.8mm).
- Back View (Right):** Shows the reverse side of the flange with a central hole of 100mm diameter. The outer diameter is 7 1/4" (183.8mm). The flange has a thickness of 5/16" (130mm). The distance from the center to the outer edge is 5 1/8" (130mm). The distance from the center to the inner hole is 4 1/4" (116mm). The distance from the center to the outer edge of the flange is 3 3/4" (99mm).

Note: "PS"=white, "BL"=black

Impedance	4Ω@1kHz 1V
Frequency	120±20% Hz
Output Sound Pressure Level	82dB
Characteristic Sensitivity	±3dB
Effective Frequency Band	Fo~20kHz
Harmonic Distortion	< 5%
	1W 85~20kHz
Polarity	Left "+", Right "-"
Temperature Range	-20°C to 70°C / -4°F to 148°F
Rated Power	25W
Max Power	30W
4"/102mm Speaker Driver	30W black PP cone paper woofer
1½" 38mm Speaker Driver	5W hard dome tweeter speaker with black PET cone
Capacitor	4.7uF non-polar capacitor
Ingress Protection	IP55

Packaging Type	Color Gift Box
Quantity Per Box (pcs)	1
Individual Packaging Dimensions (L x H x W)	6½" x 6½" x 2¾" (160 x 160 x 60mm)
Individual Packaging Gross Weight (kg/lbs)	0.6/1.32
Individual Packaging Net Weight (kg/lbs)	0.54/1.19

Packaging Type	PE Bags
Quantity Per Box (pcs)	1
Individual Packaging Dimensions (L x H x W)	6¾" x 8¾" x ¼" (170 x 222 x 0.09mm)
Individual Packaging Gross Weight (kg/lbs)	0.051/0.112
Individual Packaging Net Weight (kg/lbs)	0.045/0.098



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.