



BETTER BATH®
ALCOVE BATH TUB
OEM INSTALLATION MANUAL

L I P P E R T
C O M P O N E N T S®

Safety Information

LCI recommends that installations only be done by a qualified technician. LCI also recommends that the technician should use appropriate personal protective equipment, such as safety glasses and gloves, during the installation process.



Failure to follow the instructions provided in this manual may result in injury, component damage, or voiding of the component warranty.

Installation

NOTE: All caulks, adhesives, sealants **MUST** be compatible with ABS.

1. To avoid damage to apron, stand pan on side to install strainer.
2. Install strainer – excessive tightening of lock ring is not required and could cause damage to drain area. Do not use sharp object to remove excess caulk from around top of strainer.
3. Construct alcove with proper placement and construction of:
 - A. Access Hole: The size and shape may vary according to individual manufacturer. The access hole should be cut as small as possible to allow full support of the pan foam bottom at drain area. (1 ½" of pan foam bottom extending over access cutouts is acceptable).
 - B. Threshold Support (if applicable): The front of the pan is to be supported. Material for construction should not exceed 1 ½" overall thickness. (Note: Do not exceed 2 ¼" on 3548 and 3560 Pans.)
4. Set pan in place. Ensure bottom foam support sets securely on floor. Areas of importance are:
 - A. Floor **MUST** be flat, level, and solid.
 - B. Apron is set properly into "F" strip.
 - C. Threshold support at proper height.

NOTE: If shim is used for proper floor contact, it should support the entire foam base of pan. Partial shims should not be used and pan should be level for proper drainage.

5. Secure pan to walls using flat-back non-rusting screws. It is suggested that pan not be secured until the alcove walls are in place and secured. Ensure alcove walls are plumb, straight, and square before securing pan flanges. Flange stress, bowl deflection, and/or bottom deflection can result from moving or repositioning a wall with the pan partially attached.
6. Flat-back non-rusting screw method;
 - A. If wall does not touch flange, a shim should be used to prevent flange distortion.
 - B. Pre-drill oversized hole for screws
 - C. Stand in pan while installing screws.
 - D. Use flat-back non-rusting screws
 - E. Use only two (2) screws per flange
 - F. Screws are to be inserted 90 degrees to the wall in center of flange.
 - G. Do not screw through corners (minimum 3" from corners).
 - H. Tighten the screw until the screw back touches the flange and stop. Do not over tighten so as to distort/stress the flange.
7. Connect drain line to pan strainer after installation is complete. P-trap should connect to strainer or tail piece without requiring force or causing back pressure to drain line.
8. Clean properly. Do not use any non-recommended cleaners (see "Care and Cleaning Instructions").

Care and Cleaning Instructions

LCI Thermoforming units are easy to keep clean and sparkling. Simply use warm water and a mild soap solution. Rub with a soft cloth and rinse thoroughly with warm water. Do not use abrasive cleaners or harsh chemicals.

Recommended Cleaners: Mild soap and water, Fantastic Spray Cleaner, Top Job Liquid (3% solution), Spic and Span Pine Cleaner, Joy Liquid Detergent (5% solution), Gel-Gloss, "The Works" Tub and Shower Cleaner, DuPont 7 Auto "Polish," and DuPont 606S Auto "Polish." All cleaning should be followed by a warm water rinse.

Do Not Use: Disinfectant sprays, disinfectant foams, pine oil cleaners, citrus-based cleaners, abrasive cleaners, harsh chemicals, Scrubbing Bubbles, petroleum-based products, auto rubbing compounds or industrial or commercial cleaners.



If any adverse chemicals, as described in the Care and Cleaning Instructions, come in contact with any surface, immediately rinse thoroughly with clean water.

With the exception of Permalux® and Permalux Plus® products, fading or discoloration may result from continued exposure to direct sunlight. Keep blinds or drapes closed during periods of the day when the product is exposed to direct sunlight.

Do not place any hot objects or objects such as candles or cigarettes on the surface of this product. These objects may scar, burn or ignite this plastic.



L I P P E R T C O M P O N E N T STM

The contents of this manual are proprietary and copyright protected by Lippert Components, Inc. ("LCI"). LCI prohibits the copying or dissemination of portions of this manual unless prior written consent from an authorized LCI representative has been provided. Any unauthorized use shall void any applicable warranty. The information contained in this manual is subject to change without notice and at the sole discretion of LCI.

Revised editions are available for free download from lci1.com.

Please recycle all obsolete materials.

For all concerns or questions, please contact
Lippert Components, Inc.

Ph: (574) 537-8900 | Web: lci1.com | Email: customerservice@lci1.com



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.