

STEPS

Purpose

This document describes the removal and replacement of the KwikEE® Revolution Series step motor.

NOTE: This information was obtained from KwikEE manual #82-ST0502 Rev 0B dated July 2013.

Required Resources

- Standard automotive style jack or jack stand
- 5/16" hex driver
- 5/16" torque wrench
- 5/16" socket with ratchet

Replacement Kit #380073	
Part #	Description
369340	Motor for TT Revolution
369091	Hex Bolt, 5/16" x 2"
360212	Plastic Spacer

Instructions

⚠ WARNING

Steps MUST be supported with the proper automotive style jack or jack stand that is in good working order. If the step is not supported when the motor is removed, the step will open. Failure to properly support the steps may result in death, serious personal injury or severe product damage.

Read and understand all of the following instructions before beginning this procedure.

NOTE: This procedure must be completed with the steps either in the full retracted position or completely removed from the coach.

1. Using a standard automotive type jack or jack stand, brace the steps in the completely retracted position (Fig. 1). This will prevent the steps from opening when the motor is removed from the step.
2. Position the standard automotive type jack or jack stand to the rear of the steps. Leave some space between the step frame and the jack or jack stand to allow for later adjustment when installing the motor (Fig. 2).

Fig. 1



Fig. 2



STEPS

⚠ CAUTION


Moving parts can pinch, crush or cut. Keep clear and use caution.

Removing the Motor

The motor is attached to the step frame using three $\frac{5}{16}$ " hex bolts. On the bottom side of the motor, each bolt goes through a plastic motor spacer (Fig. 3). These spacers are not attached to the motor and will fall out when the bolt and/or the motor is removed.


1. Disconnect the 2-wire power motor harness from the motor plug. It may be necessary to use a $\frac{5}{16}$ " socket with ratchet to loosen the hex bolts used for mounting the motor.
2. Completely remove the three hex bolts (Fig. 4).

Fig. 3



Plastic Spacer
(Total of 3)

Fig. 4



$\frac{5}{16}$ " Hex Bolts

STEPS

Installing the New Motor

1. Insert three $\frac{5}{16}$ " hex bolts (Part #369091 of Kit #380073) into the motor mounting holes.
2. Place one plastic spacer (Part #360212 of Kit #380073) on each hex bolt on the backside of the motor. Each spacer has a groove on one side that must be aligned with the bolt hole (Fig. 5).

NOTE: While installing the motor, make sure to keep the three hex bolts from falling out of the mounting holes and the three plastic spacers from slipping off the end of each bolt.

3. The motor pin (Fig. 6) must be fitted into the motor mounting bracket. The step frame may need to be adjusted to ensure the proper fit of the motor.

Fig. 5





Fig. 6



STEPS

4. Verify that the motor gear is properly engaged with the drive gear mechanism (Fig. 7).
5. If the motor pin and the hex bolts do not line up properly, loosen—but do not remove—the hex bolts (Fig. 8).
6. Install the motor.
7. While holding the motor in place, tighten the hex bolts to 80 in-lbs.
8. With the motor fitted properly, use the $\frac{5}{16}$ " hex driver to tighten the bolts.

NOTE: Be careful. Do not tighten the hex bolts all the way down.

9. Use the $\frac{5}{16}$ " torque wrench to finish tightening all hex bolts down to 18 in-lbs.

NOTE: Do not overtighten!

10. Reconnect the 2-wire power motor harness to the motor. Remove the jack or jack stand from the step. Test the extension and retraction of the step.

Fig. 7





Fig. 8





KWIKEE® REVOLUTION SERIES STEP MOTOR REPLACEMENT INSTRUCTIONS (82-ST0502)

TI-273

STEPS

Support Documentation

Document #	Description
Kwikkee #1422279 / LCI #369410	Kwikkee 888 Electric Step Owner's Manual
82-ST0500	Kwikkee IMGL Step Control Testing Procedure
82-ST0501	QR-034, Kwikkee Step Identification and Replacement Parts Guide
Kwikkee #3010002262 / LCI #375656	Kwikkee Revolution Step Series Owner's Manual

As a supplier of components to the RV industry, safety, education and customer satisfaction are our primary concerns. Should you have any questions, please do not hesitate to contact us at (574) 537-8900 or by email at customerservice@lci1.com. Self-help tips, technical documents, product videos and a training class schedule are available at lci1.com or by downloading the MyLCI app.



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.