

DOORS

Resources Required

- Fabric Patch Kit (Part #441619)
- Isopropyl Alcohol
- Goggles
- Rubber Gloves
- Apron

⚠ WARNING

See the Isopropyl Alcohol warning label for appropriate cautions and warnings (Fig. 1).

Fig. 1



Installation

1. Locate tear in fabric.
2. Clean the torn area with isopropyl alcohol on both sides of the fabric. Make sure to overlap the damaged area by at least 1 inch on all sides.
3. Remove and discard the backing from the fabric patch.
4. Apply the patch to the damaged area of the fabric.
5. Press and hold the patch to the damaged area with both hands (one on each side of the fabric) to firmly adhere the self-adhesive patch.
6. Repeat steps 3 - 5 on the other side of the fabric with the second provided patch.

As a supplier of components to the RV industry, safety, education and customer satisfaction are our primary concerns. Should you have any questions, please do not hesitate to contact us at (574) 537-8900 or by email at customerservice@lci1.com. Self-help tips, technical documents, product videos and a training class schedule are available at lci1.com or by downloading the MyLCI app.



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.