

AWNINGS

Purpose

This document describes the procedure to remove wrinkles from any style awning (Fig. 1).

Fig. 1



Safety

⚠ WARNING

Always wear eye protection when performing service or maintenance to the unit. Other safety equipment to consider includes hearing protection, gloves and possibly a full face shield, depending on the nature of the service.

⚠ CAUTION

Moving parts can pinch, crush or cut. Keep clear and use caution.


Resources Required

- Socket wrench
- Appropriate sockets
- Step ladder
- Tape measure

Procedure

1. Open the awning fully.
2. Remove the fasteners (Fig. 2A) securing the awning (Fig. 2B) to the awning rail (Fig 2C). Retain fasteners for reinstallation.


Fig. 2



AWNINGS


3. Check to make sure the awning is tight across the roll tube (Fig 3A). Pull the awning close to the valance seam (Fig. 3B) and pull side-to-side to tighten on the roll tube.

Fig. 3



4. Check to make sure the awning is square by taking two diagonal measurements (Fig. 4) from awning rail to roll tube. The measurements should be within 1/8" of each other. If awning is square, skip to step 6.
5. Square the awning by pulling it side-to-side along the awning rail. If the awning cannot be squared, it will need to be replaced.

Fig. 4



6. Open and close the awning three times. This should smooth out the awning on the roll.
7. After the last time closing the awning, open it about six to eight inches. If the awning is still not completely smooth, open the awning completely before completing the rest of the procedure.
8. Go to one end of the awning and pull it outward along the awing rail about 1/8" to tighten the fabric and secure it with the previously removed fastener.
9. Pull on the other end of the fabric, then secure with the previously removed fastener.

NOTE: If the above procedure does not remove the wrinkles from the awning, the awning should be replaced.

As a supplier of components to the RV industry, safety, education and customer satisfaction are our primary concerns. Should you have any questions, please do not hesitate to contact us at (574) 537-8900 or by email at customerservice@lci1.com. Self-help tips, technical documents, product videos and a training class schedule are available at lci1.com or by downloading the MyLCI app.



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.