

KITCHEN AND BATH

Purpose

This document outlines the procedure to winterize an RV faucet to prevent damage to the faucet.

Safety

WARNING

The "WARNING" symbol above is a sign that a procedure has a safety risk involved and may cause death or serious personal injury if not performed safely and within the parameters set forth in this manual.

WARNING

Do NOT use automotive antifreeze to winterize potable water systems. Such solutions are highly toxic. Ingestion may cause serious injury or death. Use only propylene glycol-based antifreeze specified for RV winterization. Follow all product safety precautions to avoid personal injury or damage to the unit.

Procedure

1. Open all water valves in the unit.
2. Use a pressurized hose to run RV-specific antifreeze through the faucet system.

NOTE: To be effective, the antifreeze must run through the entire faucet system until it flows from the faucet.

3. Run antifreeze on cold side until all water is removed from lines and only antifreeze is coming from faucets.
4. Run antifreeze on hot side until all water is removed from lines and only antifreeze is coming from faucets.
5. Close all water valves in unit.
6. Cover faucet tip with plastic to ensure antifreeze does not drip from faucet.



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.