

200 WATT MONOKRISTALLINE FALTBARER SOLARKOFFER

Maximale Leistung: 200W

Leerlaufsspannung: 21,8 V

Short Circuit Current: 11,7A

Optimale Betriebsspannung: 18,5V

Optimaler Betriebsstrom: 10,5A

Betriebstemperatur: -40° C zu 90° C

Dimension: 90,4 x 65,8 x 7,9 cm

Gewicht: 16,2kg

RENOGY 20A VOYAGER LADEREGLER

Nennspannung: 12 VDC

Nennladestrom: 20A

Max. PV Eingangsspannung: 26 VDC

Erdung: Allgemeine Negative

Selbstverbrauch: $\leq 8\text{mA}$

Betriebstemperatur: -40° C bis 85° C

Dimension: 16,2 x 9,7 x 3,4 cm

Gewicht: 0,4kg

GARANTIE

Module

25-Jahre Leistungsgarantie:

5 Jahre / 95% Wirkungsgrad, 10 Jahre/90% Wirkungsgrad;25-Jahre/80% Wirkungsgrad

3-Jahre Material-und Verarbeitungsgarantie

Zubehöre 1-Jahr Materialgarantie



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.