

ROVER 20 AMP MPPT SOLAR LADEREGLER

Nennsystemspannung: 12V/24V Selbst Erkennung

Nennbatteriestrom: 20A

Nennlaststrom: 20A

Max. PV Eingangskurzschlussstrom: 25A

Max. Batteriespannung: 32V

Max Solar Eingangsspannung: 100 VDC

Mounting Oval: 0,76 x 0,46cm

Nettogewicht: 1,38kg

Entladestromkreis Spannungsabfall: $\leq 0,15V$

Gesamtmaße: 21 x 15 x 6cm

GARANTIE

Laderegler

2-Jahr Materialgarantie

BT1

Kommunikationsprotokoll: RS232

Porttyp: RJ12

Eingangsspannung: 5V

Schutzart: IP54

Standby-Stromverbrauch: 0,04W

Betriebsstromverbrauch: 0,05W

Kommunikationsbereich: $\leq 24m$

Serielle Baudrate: Feste Baudrate 9600bps

Kabellänge: 5,00 m

Dimension: 67.3 X 35 X 14 mm

Installation Dimensions: 67,3 ϕ 3,5mm (2.66 ϕ 0.14in) Betriebstemperatur: -20°C~85°C

Gewicht: 130g

GARANTIE

Zubehör 1-Jahr Material-Garantie



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.