



NEW EDITION VOYAGER 10A/20A PWM WATERPROOF CHARGE CONTROLLER



RENOGY NEW EDITION VOYAGER 10A/20A PWM WATERPROOF CHARGE CONTROLLER

Featuring a bright blue back-lit LCD displaying system information including error codes, the Voyager 10/20-amp charge controller is engineered to be of world-class quality. Not only is it waterproof, but it is also equipped with advanced PWM technology suitable for 12V and 24V off-grid applications, and compatible with 4 different battery types, including Lithium! Ensure your system's longevity and stay worry-free as the Voyager also has you covered with multiple solar panel, battery, and controller protections. It's the perfect solar panel accessory.

KEY FEATURES

- 12V / 24V Battery Compatibility with Auto Recognition
- Smart 4 Stage PWM charge controller: Bulk, Absorption, Float, and Equalization.
- 4 Battery Type Compatibility – Sealed/AGM, Gel, Flooded, and Lithium batteries (with Lithium Awakening feature)
- Watertight design with Backlit LCD display for system information and error codes.
- Multiple protection features for battery, controller, and solar panels (including reverse polarity and more)



RENOGY.COM



2775 EAST PHILADELPHIA ST. ONTARIO, CA 91761

Specifications

Electrical Parameters	VOYP10		VOYP20	
System Voltage	12V/24V Auto			
Battery Rated Current	10A		20A	
Max Battery Voltage	32V			
PV Input Voltage Range	15V – 55V VOC			
Max PV Input (Voc)	12V @ 25 VOC 24V @ 55VOC			
Max Power Input	12V @ 130W 24V @ 260W		12V @ 260W 24V @ 520W	
Power Consumption	12V @ 0.22W 24V @ .72W		12V @ .24W 24V @ 74W	
Battery Types	SLD/AGM, GEL, FLD, LI			
Electronic Protections	Reverse Battery polarity, Reverse PV polarity, PV Over-voltage, Battery over-voltage, PV over-current, Battery over-current, Controller over-temperature			
Grounding Type	Positive			
Controller Terminals	20-6 AWG, 2-pin terminals			
Temperature Compensation	-3mV/°C/2V, excludes LI			
Operating Temperature	-31°F ~113°F			
Storage Temperature	-31°F ~ 167°F			
Operating / Storage Humidity	10% ~ 90%, No Condensation			
Protection Level	IP67			
Dimensions	6.08 x 3.83 x 1.40 in			
Weight	.55 lbs			

Electrical Parameters	GEL	SEALED	FLOODED	LITHIUM
High Voltage Disconnect	16 V	16 V	16 V	16 V
Charging Limit Voltage	15.5 V	15.5 V	15.5 V	15.5 V
Over Voltage Reconnect	15 V	15 V	15 V	15 V
Equalization Voltage		14.6 V	14.8 V	
Boost Voltage	14.2 V	14.4 V	14.6 V	14.2 V (User: 12.6-16 V)
Float Voltage	13.8 V	13.8 V	13.8 V	
Boost Return Voltage	13.2 V	13.2 V	13.2 V	13.2 V
Low Voltage Reconnect	12.6 V	12.6 V	12.6 V	12.6 V
Under Voltage Recover	12.2 V	12.2 V	12.2 V	12.2 V
Under Voltage Warning	12 V	12 V	12 V	12 V
Low Voltage Disconnect	11.1 V	11.1 V	11.1 V	11.1 V
Discharging Limit Voltage	10.8 V	10.8 V	10.8 V	10.8 V
Equalization Duration		2 Hours	2 Hours	
Boost Duration	2 Hours	2 Hours	2 Hours	





This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.