

020-0750
Flush Mount Pull Handle -
Locked Rigid



TriMark®



This flush mount pull handle was specifically designed for compartment and entrance doors for off-highway vehicles. It offers ergonomic function and styling, is adaptable for power door lock actuation and has a "locked-rigid" handle when locked. The design provides for ease of operation by keying alike with other TriMark products with the KeyOne™ Plus lock.

DESIGNED FOR:

- Light to medium agricultural and construction personnel and compartment doors

Global Locations:

TriMark Corporation
500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058
www.trimarkcn.com



TriMark. Interactive. Product. Selector





020-0750 Flush Mount Pull Handle - Locked Rigid

FEATURES/BENEFITS:

- Ergonomic function and styling
- KeyOne™ Plus lock cylinder can be keyed alike with most single and reversible key systems
- Paddle is "locked rigid" when locked
- Adaptable for power door lock actuator
- Housing flange and internal gaskets provided for resistance to water and dirt infiltration



AVAILABLE:

- Right and left hand configuration
- Can be keyed alike with most single and reversible key systems
- Locking version

MATERIAL:

- Housing: glass reinforced black nylon, brass threaded mounting studs
- Handle: glass reinforced black nylon
- Pivot plate: mild steel

FINISH

- Black housing, black nylon handle
- Zinc plated clear chromate steel components


INSTALLATION:

- Easy mounting with (2) M6 nuts
- Recommended mounting fastener torque 30-40 in-lbs (3.3 - 4.4 N-m)
- Either horizontal or vertical orientation
- Non-handed standard mounting bracket (sold separately)

U.S. Patent No. 6,805,388

CAUTION: Product does not meet the locking requirements for FMVSS 206 (ECE R11).

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.





This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.