

Product Performance Summary

130-0100 Door Hold Open

Maximum working Load (tensile):

1334 N (300lbf.)

Maximum Tightening Torque on Mounting Fasteners:

3.39 N·m (30 in-lbs.)

Operating Temperature Range:

-40 °C (-40 °F) to 60 °C (140 °F)

Water resistance:

100%

Flammability Rating:

UL94-HB

NOTE:

The Product performance values shown are intended to be applied as a general guideline only, as specific applications and installation may affect the results. It is recommended that the Customer request a sample and conduct their own testing to determine the suitability of the Product for the intended purpose and specific application. Strength data is given as maximum loads at which the product is operable, however no safety factor has been applied.

Additional Testing information is available upon request.



500 Bailey Avenue
P.O. Box 350
New Hampton, IA 50659
United States
Tel: +1 641-394-3188
Fax: +1 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker Road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.