

Product Performance Summary

550-0100 Power Lock Actuators

Cycle/Durability:

Minimum life cycle of 50,000 cycles, maximum of 100,000 cycles.

Ingress Protection (IP) Rating—Water/Dust:

IP54, per IEC 60529, ISO 20653.

Burn Requirements Per FMVSS 302:

Material specifications verified.

Corrosion Protection:

1000 hours protection, per ASTM B117.

Environmental:

Meets -40 to 85 C testing per IEC 60068-2-1.

- Humidity at operating temp
- Operating voltage cycle
- Mechanical cycle
- Storage humidity per IEC 60068-2-14

NOTE:

The Product performance values shown are intended to be applied as a general guideline only, as specific applications and installation may affect the results. It is recommended that the Customer request a sample and conduct their own testing to determine the suitability of the Product for the intended purpose and specific application. Strength data is given as maximum loads at which the product is operable, however no safety factor has been applied.

Additional Testing information is available upon request.



500 Bailey Avenue
P.O. Box 350
New Hampton, IA 50659
United States
Tel: +1 641-394-3188
Fax: +1 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker Road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530



This manual is provided courtesy of **RV Tech Cheat Sheet**



Professional resources for the whole RV industry — free.

We put manuals, wiring diagrams and hard-won tech knowledge in every technician's hands, so repairs get done right the first time, techs work faster, and RV owners everywhere get better service.



rvtechcheatsheet.com/manuals

Find thousands more RV manuals, wiring diagrams and parts lists

RV techs: share fixes, ask questions and learn from each other.

Join our free Facebook group →



Follow proper safety practices. If in doubt, consult a professional RV technician.